nbcmeshtec.com info@nbcmeshtec.com US (800)235-5056 Int'l (630)293-5454 Fax (630)293-5647

product solution

Grünig G-STRETCH 215 Pneumatic Stretching Machine

The G-STRETCH 215 is an efficient and user-friendly pneumatic stretching machine. The mesh is automatically stretched by means of pneumatic stretching clamps.

The simple and easy-to-use standard control module contains three separate circuits regulating the X, Y and Z axes. This allows for individual adjustment of the stretching power and speed. Additionally, the stretching power needs only to be adjusted for the first screen of a series. The clamps themselves are actuated by means of two manual switches, one controlling the X/Y axes (mesh tension), and the second for the Z axis (frame contact pressure).



The programmable touchscreen control unit in the G-STRETCH 215A variant (See *Version A2* product option below) adds precision automation in the form of 50 configurable stretching programs, each with up to 10 predefined stretching cycles.

The G-STRETCH 215 can be adjusted in seconds to a range of screen sizes, from large to very small.

FEATURES

- Maximum frame format 118" x 118" in (3000 x 3000 mm)
- Instant adjustment of the machine size
- Automatic pre-bowing of the screen frames
- No contact between frame and mesh during stretching process
- Pneumatic stretching with highest precision
- A support board allows stretching of multiple frames simultaneously

PRODUCT OPTIONS

Version A1

Pneumatic stretching device for manual operation

Version A2 (G-STRETCH 215A)

Fully automatic and programmable touchscreen control system

US (800)235-5056 Int'l (630)293-5454 Fax (630)293-5647

product solution

Grünig G-STRETCH 215 Pneumatic Stretching Machine

Option W

This option consists of a wooden board with either 4,6 or 9 adjusting plates (to be selected) for CD screen frames. This allows a precise setting of the desired stretching angle in increments of 0, 7.5, 15 and 22.5 degrees.

Option Z

Additional screen frame support can be attached to two or four sides for increased contact pressure when a support plate is inserted into the machine in order to stretch several small screen frames at the same time.

PRODUCT IMAGES




Two Frames Stretched Simultaneously



Large Format Screen Support




G-STRETCH 215A Variant with Programmable Touchscreen Control Unit



G-STRETCH 208P1 Pre-Bowing Device Installed



Optional Support Plate (Option Z)




G-STRETCH 215A Variant Programmable Touchscreen Control Unit

nbcmeshtec.com info@nbcmeshtec.com US (800)235-5056 Int'l (630)293-5454 Fax (630)293-5647

product solution

Grünig G-STRETCH 215 Pneumatic Stretching Machine



G-STRETCH 215A Dimensions (mm)