

product solution


SignTronic StencilMaster® STM-ONE Series

The STM-ONE Series includes SignTronic's compact, entry-level computer-to-screen direct exposure systems based on the fourth generation of StencilMaster direct exposure technology. Designed primarily for small quantities and small format screens, they bring improved print quality, greater efficiency and lower screen costs to your print process. Precision ZEISS optics offer excellent light transmission and high precision resolution.

The STM-ONE system does not include the IN-LINE automation capabilities of other SignTronic series. However, it can still be conveniently loaded from the front and requires less space for installation.

The STM-ONE Series offers two options for the UV light source: A conventional CPL 330W UV lamp, or SignTronic's UV-LED DUO unit. While both options provide optimized UV exposure levels, the CPL 330W lamp emits a wider range of the UV spectrum, allowing for better performance with dual cure emulsions and a wider variety of meshes.

Additionally, the optional Remote Image Control Board (RICB) provides a simple and efficient means of monitoring and maintaining a high quality exposure. Each time an STM-ONE Series unit is switched on, the RIBC automatically measures the distance between the exposure head and the screen, as well as other important optical parameters, and makes any needed adjustments. This process can be repeated throughout extended runs to ensure consistent exposure. It can even compensate for bowed screens.



FEATURES

- Multiple image production for smaller screens
- Compact and space saving
- High quality steel construction
- Bidirectional imaging in both directions for speed
- Up-to-date Windows 10 operating system

PURCHASING OPTIONS

STM-ONE_S

product solution

SignTronic StencilMaster® STM-ONE Series

- Max screen size (H x W): 47.2" x 47.2" (1200 x 1200 mm)
- Max exposure size (H x W): 39.3" x 39.3" (1000 x 1000 mm)
- Standard 1270 dpi resolution (Non-upgradeable)

STM-ONE_L

- Max screen size (H x W): 47.2" x 63" (1200 x 1600 mm)
- Max exposure size (H x W): 39.3" x 55.1" (1000 x 1400 mm)
- Standard 1270 dpi resolution (Non-upgradeable)

PRODUCT OPTIONS

RIP software

Colorgate Productionserver (SignTronic Edition)

Proofing software

FirstPROOF PRO

Process control

RICB (Remote Image Control Board)

UPS (Un-interruptible Power Supply)

Available upon request


Exposure Light Source

High powered CPL 330 W UV lamp, UV-LED DUO (385 nm / 405 nm)



product solution

SignTronic StencilMaster® STM-ONE Series

PRODUCT IMAGES



SignTronic StencilMaster® STM-ONE Series with Desk



Dimensions